IW-RS104-02SN

1U Storage Rackmount Server Chassis

Features & Benefits

- External 3.5" x 4 or 2.5" x 4 hot-swap HDD trays with lock supported
- Internal 2.5" x 2 HDD Support
- Easy-swap 4028 mm PWM fans with Anti-Vibrationmechanism
- Built in Info-Tag for systems easy management
- Supports 6Gb/s SATA/SAS or 12Gb/s Mini-SAS HD backplane

Specifications

Standard	EIA-RS310D
M/B Form Factor	ATX (12" x 10")
Dimensions (D x W x H) w/o Front Panel	533.4 x 482.6 x 44.4 mm (21" x 19" x 1.75")
Drive Bay	External: Slim ODD x 1 or 2.5" x 1 (Optional), Hot-Swap 3.5" x 4 or 2.5" x 4 Internal: 2.5" x 2
Power Supply	Supports ▪ Form Factor: Flex, 1U single, 1U 1+1 Redundant PSU ▪ Watt: Flex up to 400W,Single 500W, Redundant up to 300W
Indicator	Power Status, HDD, LANs, System Fail Activity LEDs
Front Control Panel	Power Switch, ID Switch, System Reset, NMI, USB 3.0 x 2
Backplane	▪ SATA x 4 (6Gb/s Supported) ▪ Mini SAS HD(12Gb/s Supported)
Cooling Fan	Supports 40 x 28 mm PWM Easy-Swap Fan x 6
Expansion Slot	Full Height PCI Slot x 1 (via riser card and bracket)
Material	Material: SGCC Thickness: 1.0 mm
Rail Kit	Supports 28" Ball-bearing slide rail
Packaging Dimensions (D x W x H)	700 x 570 x 180 mm
Shipping Information	Net Weight: 5.63 kg Gross Weight: 9.11 kg Container Info ▪ Single Packing with pallets: 20': 384pcs, 40': 800pcs, 40'H: 900pcs

* The actual product is subject to change without prior notice. In Win Development Inc. reserves the right to make final modifications.
* Above image for reference only. All hardware components are not included.