



Features & Benefits

- Top-load design supports 72x hot-swap 3.5" LFF dual-port SAS bays in JBOD enclosure
 - Tool-less HDD captive tray slots for quick maintenance
- Features external cable management for easy access to the entire storage system
 - UI for remote system management (via GbE port)
 - 1100W PSU + fan modules with individual hot-swappable fan modules
- Opposite-facing HDD bays to offset torques and minimizes rotation vibration aggregation
 - Hot-swappable, exhaust cooling modules for optimal airflow and cooling efficiency



Specifications

Industry Standard	EIA-RS310D
Storage	External hot-swap 3.5" x 72 (SAS 12Gb/s)
Power Supply	Supports: • Form factor: high-efficiency redundant PSU • Watt: 1100W
12G Expander Module	1 or 2
Cooling Fans	80 x 38mm x 6
Host/Expansion Port	6 x Mini SAS HD (SFF-8644) for each 12G expander module
Management	Smart fan, thermal monitor, HDD monitor, voltage monitor, alarm warning
SES	Supports SES-2 (SCSI enclosure service)
Maintenance	Supports management by ethernet (optional) and RS-232
HDD Power Management	HDD sequential power on
Temperature	0°C to 35°C
Material	• Material: SGCC • Thickness: 1.0mm
Rail Kit	Supports 28" tool-less & ball-bearing slide rail
Product Dimensions (DxWxH; Chassis Only)	914.4 x 482.6 x 176mm (36" x 19" x 7")
Package Dimensions (DxWxH)	1180 x 666 x 687mm
Weight	• Net weight: 56.49kg • Gross weight: 70.89kg
Cubic Feet	19.07
Container Information	Single packing with pallets: • 20': 26pcs • 40': 54pcs

* The actual product is subject to change without prior notice. InWin Development Inc. reserves the right to make any final modifications.

* The above image is for reference only. All hardware components and optional parts are not included.