

IW-RJ472-08

Ultra Density 4U 72-Bay JBOD Enclosure

JOBD



Features & Benefits

- Top-load 2.5"/3.5" hot-swap HDD trays x 72 support SAS/SATA transfer speed.
 - Cross-position trays to limit vibrations caused by HDDs.
 - Dual-path storage for high-availability systems.
- Modular design, lower complexity, fast and easy maintenance.
- Generating intensive airflow by using four 80 x 38mm PMW hot-swap fans.
 - Web-based GUI provides the easiest way to manage JBOD system.
 - CRPS 1200W 80 Plus[®] Platinum certified.



Specifications

Industry Standard	EIA-RS310D
Drive Bay	Internal 2.5"/3.5" hot-swap trays x 72 (SAS 12Gbps, SATA 6Gbps)
Power Supply	Supports: • Form Factor: 80 PLUS Platinum CRPS • Watt: 1200W
Indicators	Status LED, drive status LEDs for bay 1-60
Front Control Panel	Power on/off, chassis ID
Cooling Fans	80 x 38mm PWM hot-swap fans x 4, 12000 RPM
SAS 12G Expander	Edge: 3 x LSI 35x36R expander support Bridge: 2 x LSI 35x48 expander support
Management	Smart Fan, thermal monitor, HDD monitor, voltage monitor, alarm warning
Host/Expansion Port	5 x Mini-SAS HD (SFF-8644) for each 12Gbps expander module
Maintenance	Supports management by Ethernet and RS-232
HDD Power Management	HDD sequential power on
Temperature	0°C to 35°C
Material	• Material: SGCC • Thickness: 1.2mm
Rail Kit	28" tool-less & ball-bearing slide rail included
Product Dimensions (DxWxH; Chassis Only)	985.75 x 447.5 x 177.1mm (38.81" x 17.62" x 6.97")
Package Dimensions (DxWxH)	1270 x 645 x 680mm
Weight (Chassis Only)	• Net weight: kg • Gross weight: kg
Cubic Feet	19.67
Container Information	Single packing with pallets: • 20': 24pcs • 40': 52pcs

IW-RJ472-08

Ultra Density 4U 72-Bay JBOD Enclosure

JOBD

I Optional Items

Item	Part Number	Description	Support
------	-------------	-------------	---------